

CARS:

- 1 a. Two point roll bar is mandatory, with two ½ bolts through upper bar then roof. No tubing to extend through firewall. All bars must be mounted on top, flat part of the frame, not on the arches.
- b. An additional two point roll bar located in front of the driver is allowed. Two ½ bolts to secure it above windshield to roof of car.
- c. Side plate for driver's door is mandatory. 12" high post-to-post, 5/16" minimum thickness fastened with six ½" bolts.
- d. Full Roll Cage is optional: No bars may extend through firewalls. No gutting of interior panels. You must have three bars minimum in driver's side, two bars minimum on passenger side. Doors may be gutted for clearance.
2. Firewall between driver and trunk area must remain in stock location. All holes must be covered.
3. A full hood, trunk lid and all outward body parts must be on the car. A. Hood may be gutted but must be secured with four hood pins.
4. All glass except front windshield must be removed. (Clean loose glass from interior)
 - a. Glass windshield may be replaced with Lexan. Lexan windshield must have three bars spaced no more than 17 inches apart.
5. Remove headliner, floor carpet, back seat and all interior trim panels.
6. Do chain or weld all doors closed.
7. Engine accessories or belts may be removed. Example: air-pump, alternator, air compressor or condenser. Window regulators may be removed.
8. Do not remove any metal interior body panels or padded dash.
9. No gutting of doors, trunk lids, wheel housing, dashes, floor pans or roofs.

SAFETY RULES:

1. 95 SNELL or NEWER helmet, approved racing belt and harness.
2. SEAT: Bench, Bucket or Racing. MUST PASS INSPECTION.
3. Firewall must remain in stock location.
- 4.* Flame retardant uniforms are required at all times when car is on race track. Tops and bottoms. Firewall between driver and fuel cell. Fuel Cells are recommended.
5. Stock Tanks are legal, unless Stock Tank is low and close to the rear bumper; in this case, Fuel Cells are Mandatory for all cars. All Stock Tanks must pass safety inspection.
6. Battery may be installed adjacent to fuel cell, minimum 3" and may be located in the driver's compartment or beneath the hood. If the battery is located in the driver's compartment, it must be boxed in by a steel or plastic closure preventing acid-spill in the event of a roll over.

GENERAL RULES:

1. Cars will be lined up by the Sportsdrome's APPN System. After two Dromer B feature wins, the winner advances to A feature by either actual APPN or placement on the poll.
2. The track reserves the right to claim a car for \$300.00.
3. Cars must go through and pass mandatory tech to be eligible to race.
4. It is the responsibility of the car owner, driver and/or mechanic to disassemble items for inspection, if requested by Officials.
5. ELIGIBILITY: Anyone minimum 16 years of age.
6. DROMER OVAL: Numbers on cars must be at least 18" high by a minimum of 2" thick, on both side doors and one large number reading back to front on the roof of the car. Also, a small number in the upper right side windshield.

**** ALL RULES ARE SUBJECT TO OFFICIALS DECISIONS ****